

Technical Features:

- 1) High system gains.
- 2) Full duplex and double-end design, external power supply, and convenient installation.
- 3) ALC technology with auto-steady function adopted.
- 4) Provide power indication and uplink and downlink indications.
- 5) With the amplified linear power, the intermodulation and spuriousness are suppressed effectively.
- 6) The reliability conforms to GB6993-86 standards.
- 7) The electromagnetic compatibility conforms to ETS300 609-4 standards.



GSM900&3G(UMTS)2100Mhz Dual Band Signal Booster

Model #		TE-903GC	TE-903GBB	TE-903GA
Frequency range		Uplink 890-915MHz/Uplink 1960-1980(MHz) Downlink 935-960 /Downlink 2110-2170MHz		
Gain (dB)	GSM Uplink	Gp≥55	Gp≥65	Gp≥45
	GSM Downlink	Gp≥60	Gp≥80	Gp≥60
	3G Uplink	Gp≥50	Gp≥55	Gp≥45
	3G Downlink	Gp≥55	Gp≥70	Gp≥60
Gain adjustable range		MGC≥30dB		
Output power(dBm)		≥17	≥23	≥20
Pass band ripple		GSM ≤4dB PCS ≤15dB		
Guard band rejection		GSM (BW-60dB)≤42 MHz (BW-70dB)≤45 MHz PCS (BW-60dB)≤104MHz (BW-70dB)≤107 MHz		
I/O impedance		50Ω/N Connector		
I/O return loss		≤-10dB		
Noise figure		≤-8dB		
Intermodulation attenuation (Po=13dBm)		≤-40dBc		
Transmission Delay		≤0.5μs		
Ambient temperature		-10℃~50℃		
Power supply		AC110~220V±10% 45~55Hz		
Size		148mm×106mm×33mm		
Reliability		To the GB6993-86 standard		
Electromagnetic compatibility		To the ETS300 694-4 standard		
Function		a) Power supply LED denote b) Export power LED denote		